

Jacking Vehicle Using Pneumatic Bottle Jack

Facility:	Written By:	Approved By:	Date Created:	Date of Last Revision

Hazards Present:	PPE or Devices Required:	Additional Training Required:
Falling vehicle	Steel toed boots	
Airborne particles	Eye protection	
Pinch points	Hand protection	
Potential crushing hazard	Fall arrest and tie off	

Safe Work Procedure:

- 1) Inspect work area and ensure all hazards are clear.
- 2) Inspect air jack.
- 3) Place blocks or wheel chocks to prevent vehicle from rolling.
- 4) Set jack on firm, level grounding on top of metal blocks.
- 5) Place wooden block on top of each jack to protect undercarriage and prevent jack from slipping.
- 6) Hook up air hose to the jacks.
- 7) Press down lever to raise jacks.
- 8) Secure each jack with bolt; perform required maintenance to vehicle, and lower jack.
- 9) Remove wooden blocks, metal blocks and put away.
- 10) Remove wheel chocks from vehicle.

If an emergency situation occurs while conducting this task, or there is an equipment malfunction, engage the emergency stop and follow the lock out procedure

REPORT ANY HAZARDOUS SITUATIONS TO YOUR SUPERVISOR

Guidance Documents/Standards:	This Safe Work Procedure will be reviewed any time the task, equipment or materials change and at a minimum of every three years
MB Workplace Safety & Health Act & Regulations:	Reviewed By WSH Committee:
4 General Workplace Requirements	Date:
6 Personal Protective Equipment	
16 Machines, Tools and Robots	