

Nail Gun

Facility:	Written By:	Approved By:	Date Created:	Date of Last Revision

Hazards Present:	PPE or Devices Required:	Additional Training Required:
Trips	Eye protection	See operators manual
Misfire causing injury	Steel toe boots	
	Hard hat	
	Hearing protection	

Safe Work Procedure:

- 1) Ensure nail gun is disconnect from air supply before cleaning and inspecting.
- 2) To operate, your finger must be off the trigger and the work contact element of the nailer then pressed against the work piece.
- 3) Once the work contact element is pressed against the work piece, pull the trigger to drive the fastener into the work piece.
- 4) Release the trigger after each fastener is driven.
- 5) Move the nailer to the next location and repeat the procedure above.
- 6) Test the proper fastener penetration by driving nails into a sample piece of wood. If the fasteners do not achieve the desired penetration, adjust the air pressure to a higher setting until the desired penetration is achieved.

If an emergency situation occurs while conducting this task, or there is an equipment malfunction, engage the emergency stop and follow the lock out procedure

REPORT ANY HAZARDOUS SITUATIONS TO YOUR SUPERVISOR

<p>Guidance Documents/Standards:</p> <p>MB Workplace Safety & Health Act & Regulations: <i>Part 6 – Personal Protective Equipment</i> <i>Part 16 – Machines and Tools</i></p>	<p>This Safe Work Procedure will be reviewed any time the task, equipment or materials change and at a minimum of every three years</p>
	<p>Reviewed By WSH Committee:</p> <p>Date:</p>