

Snow Removal

<b>Facility:</b>	<b>Written By:</b>	<b>Approved By:</b>	<b>Date Created:</b>	<b>Date of Last Revision</b>

<b>Hazards Present:</b>	<b>PPE or Devices Required:</b>	<b>Additional Training Required:</b>
Vehicle Traffic	Coveralls	Equipment Manual
Pedestrian Traffic	Hard hat with liner	
Winter Weather Conditions	Gloves	
Poor Visibility	Steel toed boots	
Icy Roads	Hi vis vest	
	Winter Clothing	

**Safe Work Procedure:**

- 1) Assess the location and observe the location to identify hazards, driveways and traffic flow
- 2) Ensure that equipment is in good operating condition
- 3) Plow snow from the road surface using a grader or truck/plow to provide reasonable winter driving conditions.
- 4) Plow after a storm unless a blockage exists or accumulation exceeds specified limits.
- 5) Flow from the center of the road out.
- 6) Continue plowing with the traffic flow, periodically stopping to allow accumulated traffic behind to pass.
- 7) Approx. 1 to 2 cm of snow cushion should be left on gravel roads.

***If an emergency situation occurs while conducting this task, or there is an equipment malfunction, engage the emergency stop and follow the lock out procedure***

**REPORT ANY HAZARDOUS SITUATIONS TO YOUR SUPERVISOR**

<p><b>Guidance Documents/Standards:</b></p> <p>MB Workplace Safety &amp; Health Act &amp; Regulations:</p>	<p>This Safe Work Procedure will be reviewed any time the task, equipment or materials change and at a minimum of every three years</p>
	<p>Reviewed By WSH Committee:</p> <p>Date:</p>