

Support Dump Boxes

Facility:	Written By:	Approved By:	Date Created:	Date of Last Revision

Hazards Present:	PPE or Devices Required:	Additional Training Required:
Serious injury/potential death	Steel toed boots	
Pinch points	Eye protection	
	Hand protection	
	Hard Hat	

Safe Work Procedure:

- 1) Park and block truck in neutral with the PTO and pump engaged
- 2) Raise truck box to desired level
- 3) A Stiff leg is a permanently attached pivot and rest, and is the preferred method of support
- 4) If not available use the following:
 - a. 6"x6"x6' long timber block across the truck frame between the box and sub frame as close as possible to the box hinge
 - b. pieces of 4"x4"x6' timber placed vertically between tandem tire and the box
 - c. Pin locks provided by the manufacturer to secure the box in the elevated position
- 5) Only keep the box lifted for as long as necessary

If an emergency situation occurs while conducting this task, or there is an equipment malfunction, engage the emergency stop and follow the lock out procedure

REPORT ANY HAZARDOUS SITUATIONS TO YOUR SUPERVISOR

<p style="text-align: center;">Guidance Documents/Standards:</p> <p>MB Workplace Safety & Health Act & Regulations:</p> <p>4 General Workplace Requirements 6 Personal Protective Equipment 16 Machines, Tools and Robots 22 Powered Mobile Equipment Safe Work Bulletin #148</p>	<p>This Safe Work Procedure will be reviewed any time the task, equipment or materials change and at a minimum of every three years</p> <hr/> <p>Reviewed By WSH Committee:</p> <p>Date:</p>
--	---