

Tilt Deck Trailer

Facility:	Written By:	Approved By:	Date Created:	Date of Last Revision

Hazards Present:	PPE or Devices Required:	Additional Training Required:
Pinch points	CSA foot wear	
Fingers, toes	Gloves	
Tip over		
Back strain		

Safe Work Procedure:

Load:

- 1) Place item to be loaded at base of trailer
- 2) Place trailer in straight position on level firm ground
- 3) Engage tractor only maxis
- 4) Flag off lift zone for loading
- 5) Purge air trailer system
- 6) Hook up the feed and return hydraulic lines from the truck to the trailer
- 7) Engage the PTO in the truck by pushing in the clutch and a switching the
- 8) Place axels on trailer all forward
- 9) Tilt Trailer
- 10) Attach Winch li ne to item
- 11) Winch piece onto trailer
- 12) Level trailer deck
- 13) Move axels all the way back
- 14) Secure load to trailer
- 15) Switch the trailer air system back up to fill with air
- 16) Turn of the PTO
- 17) U nhook the trailer hydraulic lines

Unload:

Repeat the load process in reverse.

If an emergency situation occurs while conducting this task, or there is an equipment malfunction, engage the emergency stop and follow the lock out procedure

REPORT ANY HAZARDOUS SITUATIONS TO YOUR SUPERVISOR

Guidance Documents/Standards: MB Workplace Safety & Health Act & Regulations:	This Safe Work Procedure will be reviewed any time the task, equipment or materials change and at a minimum of every three years
	Reviewed By WSH Committee: Date: