

Unload From a Semi Trailer

Facility:	Written By:	Approved By:	Date Created:	Date of Last Revision

<b>Hazards Present:</b>	<b>PPE or Devices Required:</b>	<b>Additional Training Required:</b>
Vehicle damage	Steel toe boots	Equipment/ Procedure Training
Other workers	Safety gloves	
Equipment	Hard hat	
Slip/trip	Hearing protection	
Pinch points	Safety glasses	
	Hi visibility vest	

**Safe Work Procedure:**

- 1) Park the truck and trailer on level ground and set parking brakes.
- 2) Exit the vehicle using three point contact.
- 3) Manually disconnect the trailer from the truck.
- 4) Re-enter the truck and pull away from the disconnected trailer.
- 5) Exit the machine using three point contact.
- 6) Remove the Chain/ Straps from the Plow/ Excavator/ Dozer and place them in the storage compartment.
- 7) Inspect the area for any people or hazards that may be in the path of the plow when unloading.
- 8) Mount the Plow/ Excavator/ Dozer using three point contact.
- 9) Slowly drive off of the trailer.
- 10) Park on level ground.
- 11) Exit the machine using three point contact.
- 12) Re-enter the truck and back up to the trailer.
- 13) Exit the vehicle using three point contact.
- 14) Reconnect the trailer to the truck.

***If an emergency situation occurs while conducting this task, or there is an equipment malfunction, engage the emergency stop and follow the lock out procedure***

**REPORT ANY HAZARDOUS SITUATIONS TO YOUR SUPERVISOR**

<b>Guidance Documents/Standards:</b>  MB Workplace Safety & Health Act & Regulations: 4 General Workplace Requirements 6 Personal Protective Equipment 16 Machines, Tools 20 Vehicular and Pedestrian Traffic 22 Powered Mobile Equipment	This Safe Work Procedure will be reviewed any time the task, equipment or materials change and at a minimum of every three years
	Reviewed By WSH Committee:  Date: