

Wheel Loader Operation

Facility:	Written By:	Approved By:	Date Created:	Date of Last Revision

Hazards Present:	PPE or Devices Required:	Additional Training Required:
Vehicle traffic	Coveralls	Operators Manual
Pedestrian traffic	Hard hat	
Moving equipment	Eye protection	
Overhead wires	Steel Toed Boots	
Underground utilities	Hearing protection	
	Hi Vis Vest	

Safe Work Procedure:

- 1) Observe worksite location to identify hazards and traffic flow
- 2) Place warning signs and barricades
- 3) Ensure that the loader is in good operating condition
- 4) Do pre-trip inspection on machine and start
- 5) Check back up alarm, lights, all gauges, and hydraulics
- 6) Mount/dismount using 3-point contact
- 7) Seat belts must be worn at all times
- 8) Hearing protection to be worn at all times
- 9) Operator shall not permit any person to practice with or ride on the loader
- 10) When travelling with loader, the bucket must be at the lowest height possible to prevent tipping

If an emergency situation occurs while conducting this task, or there is an equipment malfunction, engage the emergency stop and follow the lock out procedure

REPORT ANY HAZARDOUS SITUATIONS TO YOUR SUPERVISOR

<p>Guidance Documents/Standards:</p> <p>MB Workplace Safety & Health Act & Regulations:</p> <p>Part 22 Powered Mobile Equipment 20 Vehicular and Pedestrian Traffic</p>	<p>This Safe Work Procedure will be reviewed any time the task, equipment or materials change and at a minimum of every three years</p>
	<p>Reviewed By WSH Committee:</p> <p>Date:</p>