

Attaching Skid Mounted Equipment to Tracked Equipment

Facility:	Written By:	Approved By:	Date Created:	Date of Last Revision

<i>Hazards Present:</i>	<i>PPE or Devices Required:</i>	<i>Additional Training Required:</i>
Pinch Point/Crushing	Safety Glasses	First Aid/CPR
Poor Lighting	Hearing Protection	Common Core
Communication	Steel Toed Boots	
Noise in excess of 85db	High Vis Vest	
	Hard Hat	

Safe Work Procedure:

- 1) Wear all required PPE
- 2) Complete pre-move toolbox meeting, discussing steps to complete move
- 3) Never stand between equipment and load
- 4) Communication through hand signals are key; discuss with operator hand signals to be used
- 5) Operator must release winch break and/or reverse the cable out or put winch into free spool and have the hand on the ground. Pull the cable towards the skid mounted equipment
- 6) Lift the hitch, if necessary to get help lifting
- 7) Operator now tightens the winch bale; if skids are free the skid mounted equipment is now ready to move uphill or across level terrain

If an emergency situation occurs while conducting this task, or there is an equipment malfunction, engage the emergency stop and follow the lock out procedure
REPORT ANY HAZARDOUS SITUATIONS TO YOUR SUPERVISOR

Guidance Documents/Standards:	This Safe Work Procedure will be reviewed any time the task, equipment or materials change and at a minimum of every three years
MB Workplace Safety & Health Act & Regulations: Part 6 Personal Protective Equipment Part 12 Hearing Conservation	Reviewed By WSH Committee: Date: