

Backfill from Top of a Bank

Facility:	Written By:	Approved By:	Date Created:	Date of Last Revision

Hazards Present:	PPE or Devices Required:	Additional Training Required:
Other workers and equipment	Steel toed boots	Operator Training
Machine malfunction	Hard hat	
Working on loose grounding	Safety glasses	
	Gloves	
	Safety Vest	

Safe Work Procedure:

- 1) Designate a spotter who will be responsible for directing the driver/operator to the bank and to dump load.
- 2) Check ground for stability before proceeding to top of bank.
- 3) Ensure that all other workers and equipment are aware and stay clear of dump.
- 4) Follow through with dump when spotter signals it is safe to do so.
- 5) Once load is completely dumped, lower the box and carefully pull away from the bank.

If an emergency situation occurs while conducting this task, or there is an equipment malfunction, engage the emergency stop and follow the lock out procedure

REPORT ANY HAZARDOUS SITUATIONS TO YOUR SUPERVISOR

<p>Guidance Documents/Standards:</p> <p>MB Workplace Safety & Health Act & Regulations: 6 Personal Protective Equipment 14 Fall Protection 16 Machines, Tools and Robots 20 Vehicular and Pedestrian Traffic 26 Excavations and Tunnels</p>	<p>This Safe Work Procedure will be reviewed any time the task, equipment or materials change and at a minimum of every three years</p>
	<p>Reviewed By WSH Committee:</p> <p>Date:</p>