

Chain Saw Bar Maintenance

<b>Facility:</b>	<b>Written By:</b>	<b>Approved By:</b>	<b>Date Created:</b>	<b>Date of Last Revision</b>

<b>Hazards Present:</b>	<b>PPE or Devices Required:</b>	<b>Additional Training Required:</b>
Pinch Points	Steel toed boots	
	Face shield	
	Eye protection	
	Hand protection	

**Safe Work Procedure:**

- 1) Ensure appropriate bar is used
- 2) Inspect for bolt tightness, cracks and defects
- 3) When tightening nuts on the bar, always hold bar nose up
- 4) Clean bar groove and oil hose
- 5) Ensure bar is receiving oil
- 6) Grease roller and sprocket nose
- 7) Remove any burred edges on the bar
- 8) Check bar straightness
- 9) Check for pinched or uneven bar groove
- 10) Reverse bar for uneven wear

***If an emergency situation occurs while conducting this task, or there is an equipment malfunction, engage the emergency stop and follow the lock out procedure***

**REPORT ANY HAZARDOUS SITUATIONS TO YOUR SUPERVISOR**

<p><b>Guidance Documents/Standards:</b></p> <p>MB Workplace Safety &amp; Health Act &amp; Regulations: 6 Personal Protective Equipment 16.27 Chain Saw Requirements</p>	<p>This Safe Work Procedure will be reviewed any time the task, equipment or materials change and at a minimum of every three years</p>
	<p>Reviewed By WSH Committee:</p> <p>Date:</p>