

Changing Auger Teeth

Facility:	Written By:	Approved By:	Date Created:	Date of Last Revision

Hazards Present:	PPE or Devices Required:	Additional Training Required:
Pinch points	Steel toed boots	
Muscle strain	Eye protection	
Cutting injury/amputation	Hand protection	
	Face Shield	

Safe Work Procedure:

- 1) Wear all applicable PPE
- 2) Beat out the old tooth with a sledge hammer. A pin or piece of rebar may be required to knock out tooth
- 3) Shield yourself while driving in the new tooth
- 4) Keep fingers and hands away from Kelly bar and areas where they can get jammed
- 5) Maintain periodic eye contact with the operator and make sure they are aware when you have completed task

If an emergency situation occurs while conducting this task, or there is an equipment malfunction, engage the emergency stop and follow the lock out procedure

REPORT ANY HAZARDOUS SITUATIONS TO YOUR SUPERVISOR

<p>Guidance Documents/Standards:</p> <p>MB Workplace Safety & Health Act & Regulations: 6 Personal Protective Equipment 8 Musculoskeletal Injury 16 Machines, Tools and Robots</p>	<p>This Safe Work Procedure will be reviewed any time the task, equipment or materials change and at a minimum of every three years</p> <p>Reviewed By WSH Committee:</p> <p>Date:</p>
--	--