

Fertilizer - Liquid

Facility:	Written By:	Approved By:	Date Created:	Date of Last Revision

Hazards Present:	PPE or Devices Required:	Additional Training Required:
Chemical Burns	Gloves	
Skin Irritation	Safety Glasses	
Eye Irritation	Safety Boots	
	Hi Vis Vest	

Safe Work Procedure:

- 1) Mix appropriate amount of water and liquid fertilizer according to manufacturer's directions on the product. Refer to available MSDS.
- 2) Clean up any spills immediately.
- 3) Check tank and hose for leaks before leaving base.
- 4) Drive to site using only approved routes and according to load.
- 5) Arrive at worksite.
- 6) Unravel spray hose.
- 7) Set regulator to proper distribution – if equipped.
- 8) Spray property from back to front using an imaginary grid pattern until property is fully covered.
- 9) Reel in hose.
- 10) Check tank and hose for leaks.
- 11) Drive to next site.

If an emergency situation occurs while conducting this task, or there is an equipment malfunction, engage the emergency stop and follow the lock out procedure

REPORT ANY HAZARDOUS SITUATIONS TO YOUR SUPERVISOR

Guidance Documents/Standards: MB Workplace Safety & Health Act & Regulations Part 6 Personal Protective Equipment Part 35 WHMIS	This Safe Work Procedure will be reviewed any time the task, equipment or materials change and at a minimum of every three years
	Reviewed By WSH Committee: Date: