

Gravel Resurfacing

<b>Facility:</b>	<b>Written By:</b>	<b>Approved By:</b>	<b>Date Created:</b>	<b>Date of Last Revision</b>

<b>Hazards Present:</b>	<b>PPE or Devices Required:</b>	<b>Additional Training Required:</b>
Vehicle traffic	Coveralls, Gloves	
Pedestrian traffic	Hard hat	
Slips, trips, falls	Safety Glasses	
Moving equipment	Steel toed boots	
	Hi Vis Vest	

**Safe Work Procedure:**

- 1) Assess the location
- 2) Place barricades
- 3) Blade roadway prior to application
- 4) Dump new material along one edge of roadway. Space gravel as per supervisors instructions
- 5) Cut material from dump piles with grader and blade towards opposite side of the road. Form a uniform windrow. Move windrow back and forth with grader blade to mix material.
- 6) Cut material from windrow near center and spread evenly to shoulders to give a uniform depth of new material.
- 7) Remove barricades.

***If an emergency situation occurs while conducting this task, or there is an equipment malfunction, engage the emergency stop and follow the lock out procedure***

**REPORT ANY HAZARDOUS SITUATIONS TO YOUR SUPERVISOR**

<p><b>Guidance Documents/Standards:</b></p> <p>MB Workplace Safety &amp; Health Act &amp; Regulations:</p>	<p>This Safe Work Procedure will be reviewed any time the task, equipment or materials change and at a minimum of every three years</p>
	<p>Reviewed By WSH Committee:</p>  <p>Date:</p>