

Greasing a Vehicle

Facility:	Written By:	Approved By:	Date Created:	Date of Last Revision

<i>Hazards Present:</i>	<i>PPE or Devices Required:</i>	<i>Additional Training Required:</i>
Eye injury	Steel toed boots	
Burns	Eye protection	
Potential death	Hand protection	

Safe Work Procedure:

- 1) Shut off machine; remove keys and set parking brake. Use wheel chocks for added safety
- 2) Lay on creeper with grease gun and towel, and roll under vehicle
- 3) Clean each grease fitting and apply grease.
- 4) Check for fittings that need to be replaced and for any worn joints
- 5) Clean grease gun thoroughly when finished and put all tools used away
- 6) Remove wheel chocks

If an emergency situation occurs while conducting this task, or there is an equipment malfunction, engage the emergency stop and follow the lock out procedure

REPORT ANY HAZARDOUS SITUATIONS TO YOUR SUPERVISOR

<p style="text-align: center;">Guidance Documents/Standards:</p> <p style="text-align: center;">MB Workplace Safety & Health Act & Regulations:</p> <p>4 General Workplace Requirements 6 Personal Protective Equipment 21 Emergency Washing Facilities 35 Workplace Hazardous Materials Information Systems</p>	<p style="text-align: center;">This Safe Work Procedure will be reviewed any time the task, equipment or materials change and at a minimum of every three years</p>
	<p>Reviewed By WSH Committee:</p> <p>Date:</p>