

SAFE WORK PRACTICE

TITLE	Stringing Pipeline Pipe
GENERAL	Protecting workers from injuries associated with stringing operations
APPLICATION	Pipe is loaded and transported from the place of manufacture, coating or stockpile to the pipeline right-of-way where it is off-loaded and strung.
POTECTIVE MECHANISMS	Safe work procedure Permit system Barricades and warning signs PPE ERP (Emergency Response Plan) Rigging & Hoisting Procedure Pipe Blocking Procedure
SELECTION AND USE	As per safe job procedure Provincial OH&S Legislation
SUPERVISOR RESPONSIBILITY	Supervisors are responsible to facilitate and/or provide proper instruction to their workers on protection requirements and training Hazard assessment Site inspection
WORKER RESPONSIBILITY	<ol style="list-style-type: none"> 1. Ensure you remain within the operators' line of vision. 2. Watch your step. 3. Know the proper hand signals. 4. Know pinch points. 5. Do not stand between pipe and equipment. 6. Do not stand between pipe and ditch. 7. Do not walk under suspended loads. 8. Ensure proper rigging & hoisting safe work procedures are followed. 9. Ensure proper pipe blocking safe work procedures are followed.
<p>* The information presented in this publication is intended for general use and may not apply to every circumstance. It is not a definitive guide to government regulations and does not relieve persons using this publication from their responsibilities under applicable legislation</p>	