

**SAFE WORK PRACTICE**

<b>TITLE</b>	Wheeled Articulating Loader
<b>GENERAL</b>	Protecting workers from injuries associated with the operation of a wheeled articulating loader
<b>APPLICATION</b>	Wheeled articulating loader must be operated in a safe manner to ensure the safety of operator and those around the machine
<b>PROTECTIVE MECHANISMS</b>	Safe job procedure PPE ERP Manufacturers recommendations Company rules
<b>SELECTION AND USE</b>	As per safe job procedure
<b>SUPERVISOR RESPONSIBILITY</b>	Supervisors are responsible to facilitate and/or provide proper instruction to their workers on protection requirements and training
<b>WORKER RESPONSIBILITY</b>	<ol style="list-style-type: none"> <li>1. Only properly trained and qualified persons shall operate loader</li> <li>2. All permits, line locating, and ground inspections have been performed</li> <li>3. Perform pre trip inspection of machine</li> <li>4. Wear seatbelt</li> <li>5. Do not operate machine on sever inclines, declines or slopes</li> <li>6. Follow manufacturers recommendations for cool down and shut off</li> <li>7. Dismount from machine using three point contact method</li> </ol>

\* The information presented in this publication is intended for general use and may not apply to every circumstance. It is not a definitive guide to government regulations and does not relieve persons using this publication from their responsibilities under applicable legislation